

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently Amended) A camera, comprising:

A₁
a first lens;

a second lens;

a photo-electric converting element to receive a light incoming from a subject image through said first lens and said second lens, and to convert said light into image signals;

a driving member to move said first lens and said second lens in an optical path;

[[and]]

guiding means for guiding said second lens moved by said driving member so that a distance between said photo-electric converting element and said second lens changes stepwise, wherein said driving member selectively moves said second lens to one of a plurality of predetermined positions of said guiding means during a focal length changing operation;

ranging means for measuring a distance between said camera and a subject to output a ranging signal;

a first image processor to output a first image data generated by processing said image signals which are converted from said subject image, said subject image being

received by said photo-electric converting element when said second lens is located at
a first position of said plurality of predetermined positions; and
a second image processor to output a second image data generated by
processing said first image data on the basis of said ranging signal.

A₆
ent.

2. (Currently Amended) The camera of claim 1,
wherein both [[a]] said focal length changing operation and a focus adjustment
are performed by means of said driving member.

3. (Cancelled).

4. (Currently Amended) The camera of claim [[3]] 1,
wherein said guiding means has a cam groove.

5. (Original) The camera of claim 1, further comprising:
a display for displaying images based on said image signals.

6. (Currently Amended) The camera of claim 1,
wherein said guiding means, ~~comprising~~ comprises:

first guiding means for conducting said focal length changing operation by
guiding said second lens in said optical path so as to trace a first predetermined locus in
relative to said first lens; and

second guiding means for conducting ~~[[said]]~~ a focus adjustment by guiding said second lens in said optical path so as to trace a second predetermined locus, which is different from said first predetermined locus, in relative to said first lens, wherein said second guiding means are located on an extension of said first guiding means in such a manner that said first guiding means and said second guiding means are staggered on said guiding means.

A₆
cont.

7. (Currently Amended) The camera of claim 1,
wherein said driving member moves said second lens on said guiding means during both ~~[[a]]~~ said focal length changing operation and a focus adjustment.

8. (Original) The camera of claim 1,
wherein said driving member is a single member to drive both said first lens and said second lens.

9. (Currently Amended) The camera of claim ~~[[3]]~~ 1,
wherein said driving member is a cam barrel in which cam grooves are formed stepwise on inner surface of said cam barrel.

10. (Cancelled).

11. (Currently Amended) The camera of claim ~~[[10]]~~ 1,

wherein said second image processor applies a magnification change processing to said first image data.

12. (Currently Amended) The camera of claim [[10]] 1, further comprising:
a calculator to calculate an image magnification factor, which varies between before and after said focus adjustment, on the basis of said ranging signal and information designating said first position, wherein said second image processor applies a magnification change processing to said first image data on the basis of said image magnification factor.

A₆
can't

13. (Original) The camera of claim 11, further comprising:
memory means for memorizing a plurality of image magnification factors which correspond to said plurality of predetermined positions and said ranging signals, wherein said second image processor selects an image magnification factor, corresponding to said ranging signal and information designating said first position, out of a plurality of said image magnification factors memorized in said memory means, and then, said second image processor applies a magnification change processing to said first image data on the basis of said image magnification factor selected by said second image processor.

14. (Currently Amended) The camera of claim [[10]] 1, further comprising:
an image display for displaying an image based on said image signals converted by said photo-electric converting element, wherein said focus adjustment and an image

capturing are performed after said image display displays images based on said second image data.

15. (Currently Amended) The camera of claim [[10]] 1,
wherein said second image processor performs a processing for extracting at
least a part of said first image data to generate said second image data.

A₆
Cont 16. (Original) The camera of claim 15, further comprising:
a calculator to calculate an image magnification factor, which varies between
before and after said focus adjustment, on the basis of said ranging signal and
information designating said first position, wherein said second image processor applies
a grouping processing to a peripheral region of said first image data on the basis of said
image magnification factor to generate said second image data.

17. (Currently Amended) The camera of claim [[10]] 1,
wherein said driving member moves said second lens from one of said plurality
of predetermined positions on said guiding means in such a direction that an image
frame reduces, during said focus adjustment.

18. (Currently Amended) The camera of claim [[10]] 1,
wherein a position of a maximum image frame in each of predetermined variable
power regions is located at each of said plurality of predetermined positions.

19. (Original) The camera of claim 15,

wherein said driving member moves said second lens from one of said plurality of predetermined positions on said guiding means in such a direction that an image frame reduces, during said focus adjustment.

20. (Original) The camera of claim 15,

Agent

wherein a position of a maximum image frame in each of predetermined variable power regions is located at each of said plurality of predetermined positions.

21. (Original) The camera of claim 1,

wherein said driving member is capable of moving said second lens to a storing region located at a position nearer said photo-electric converting element than a position of the shortest focal length, and image capturing is not performed when said second lens is located at said storing region.

22. (Original) The camera of claim 16,

wherein said grouping processing performed by said second image processor is to superpose a predetermined window frame on a peripheral region of an image based on said first image data.

23. (Original) The camera of claim 16,

wherein said grouping processing performed by said second image processor is to superpose a predetermined color region and/or pattern region on a peripheral region of an image based on said first image data..

24. (Currently Amended) The camera of claim [[10]] 1, further comprising:
a display for appropriately displaying images based on said first image data, said second image data and a third image data which is outputted by said first image processor after said focus adjustment.

Ab
cont
25. (Original) The camera of claim 24, further comprising:
a memory for memorizing said third image data.

26. (Currently Amended) The camera of claim [[10]] 1, further comprising:
an exposure section to expose a silver-halide film, wherein said light incoming from a subject image through said first lens and said second lens is divided into a first light and a second light, said first light is introduced to said photo-electric converting element while said second light is introduced to said exposure section.

27. (Currently Amended) ~~The camera of claim 3, further~~ A camera, comprising:
a first lens;
a second lens;

a photo-electric converting element to receive a light incoming from a subject image through said first lens and said second lens, and to convert said light into image signals;

a driving member to move said first lens and said second lens in an optical path;
guiding means for guiding said second lens moved by said driving member so that a distance between said photo-electric converting element and said second lens changes stepwise, wherein said driving member selectively moves said second lens to one of a plurality of predetermined positions of said guiding means during a focal length changing operation;

Ab
cont
a discriminator for discriminating whether said second lens is moved to a first region of said guiding means or is moved to a second region of said guiding means by said driving member; and

an image processing section to output a first image data based on said image signals if said discriminator determines that said second lens is moved to said first region, and to output a second image data generated by applying a magnification change processing to said image signals based on a predetermined zooming magnification factor if said discriminator determines that said second lens is moved to said second region.

28. (Original) The camera of claim 27, further comprising:

a memory for memorizing said zooming magnification factors, wherein said memory memorizes a plurality of zooming magnification factors which correspond to positions to which said second lens is moved.

29. (Original) The camera of claim 27, further comprising:

a display for displaying images based on said image signals, wherein said display displays images based on said first image data or said second image data during focal length changing operation.

30. (Original) The camera of claim 27,

wherein an image processing is not performed in said first region, while an image processing is performed in said second region.

Ab
ent

31. (Original) The camera of claim 27,

wherein said discriminator discriminates whether said second lens is moved to a first region of said guiding means or is moved to a second region of said guiding means by said driving member during a focal length changing operation, and said image processing section outputs either said first image data or said second image data, based on said image signals obtained after focus adjustment.

32. (Currently Amended) ~~The camera of claim 3, further~~ A camera, comprising:

a first lens;

a second lens;

a photo-electric converting element to receive a light incoming from a subject image through said first lens and said second lens, and to convert said light into image signals;

a driving member to move said first lens and said second lens in an optical path;
guiding means for guiding said second lens moved by said driving member so
that a distance between said photo-electric converting element and said second lens
changes stepwise, wherein said driving member selectively moves said second lens to
one of a plurality of predetermined positions of said guiding means during a focal length
changing operation;

a discriminator for discriminating whether said second lens is moved to a first region of said guiding means or is moved to a second region of said guiding means by said driving member; and

Ab
cont an image processing section to output a first image data based on said image signals before focus adjustment if said discriminator determines that said second lens is moved to said first region, and to output a second image data generated by applying a magnification change processing to said image signals based on a predetermined zooming magnification factor before focus adjustment if said discriminator determines that said second lens is moved to said second region.

33. (Original) The camera of claim 32, further comprising:

a memory for memorizing said zooming magnification factor, wherein said memory means memorizes a plurality of zooming magnification factors which correspond to positions to which said second lens is moved.

34. (Original) The camera of claim 32, further comprising:

a display for displaying images based on said image signals, wherein said display displays images based on said first image data or said second image data before a focal length changing operation.

35. (Original) The camera of claim 27, further comprising:

cont
A₆
ranging means for measuring a distance between said camera and said subject to output a ranging signal, wherein said image processing section outputs said first image data based on said image signals, which are obtained after performing a focus adjustment on the basis of said ranging signal from a predetermined reference position, when said discriminator determines that said second lens is moved to said first region, and outputs a second image data generated by applying a magnification change processing to said image signals, which are obtained after performing a focus adjustment on the basis of said ranging signal from a predetermined reference position, based on predetermined zooming magnification factors, when said discriminator determines that said second lens is moved to said second region.

36. (Original) The camera of claim 32, further comprising:

ranging means for measuring a distance between said camera and said subject to output a ranging signal, wherein said image processing section outputs said first image data based on said image signals, which are obtained after performing a focus adjustment on the basis of said ranging signal from a predetermined reference position, when said discriminator determines that said second lens is moved to said first region, or to output a second image data generated by applying a magnification change

processing to said image signals, which are obtained after performing a focus adjustment on the basis of said ranging signal from a predetermined reference position, based on predetermined zooming magnification factors, when said discriminator determines that said second lens is moved to said second region.

37. (Original) The camera of claim 1, wherein said guiding means guides said second lens moved by said driving member so that a distance between a focal surface of said photo-electric converting element and said second lens changes stepwise.

At
Cont 38. (Original) An image capturing apparatus being characterized in that said image capturing apparatus is provided with:

a zoom lens in which a variable power operation in a plurality of predetermined variable power regions and a focus adjustment in each of said variable power regions are performed by means of a driving action of single component driving member;

ranging means for measuring a distance between said image capturing apparatus and a subject;

a calculator to calculate an image magnification factor, which varies between before and after said focus adjustment, from a ranging signal of said ranging means and a variable power information designating a selected variable power region of said zoom lens;

a photo-electric converting element to receive a subject image by means of said zoom lens, and to convert said subject image into image signals;

a first image processor for outputting a first image data generated by processing said image signals before said focus adjustment; and

a second image processor for outputting a second image data generated by applying a magnification change processing to said first image data based on a calculation result of said calculator.

39. (Original) An image capturing apparatus being characterized in that said image capturing apparatus is provided with:

Ab
CnA a zoom lens in which a variable power operation in a plurality of predetermined variable power regions and a focus adjustment in each of said variable power regions are performed by means of a driving action of single component driving member;

ranging means for measuring a distance between said image capturing apparatus and a subject;

a calculator to calculate an image magnification factor, which varies between before and after said focus adjustment, from a ranging signal of said ranging means and a variable power information designating a selected variable power region of said zoom lens;

a photo-electric converting element to receive a subject image by means of said zoom lens, and to convert said subject image into image signals;

a first image processor for outputting a first image data generated by processing said image signals before said focus adjustment; and

a second image processor for outputting a second image data generated by applying a grouping processing to a peripheral region of said first image data based on a calculation result of said calculator.

40. (Original) An image capturing apparatus being characterized in that said image capturing apparatus is provided with:

a zoom lens in which both a zooming operation and a focusing operation are performed by means of a driving action of single component driving member, and which is driven to either a first region in which a image processing is not performed, or a second region in which a image processing is performed;

Ab
Cont a discriminator for discriminating whether said zoom lens is moved to said first region or is moved to said second region;

a photo-electric converting element to receive a subject image incoming through said zoom lens, and to convert said subject image into image signals; and

an image processing section to output a first image data based on said image signals when said discriminator determines that said zoom lens is moved to said first region, or to output a second image data generated by applying a magnification change processing to said image signals based on predetermined zooming magnification factor when said discriminator determines that said zoom lens is moved to said second region.

41. (Original) An image capturing apparatus being characterized in that said image capturing apparatus is provided with:

a zoom lens in which both a zooming operation and a focusing operation are performed by means of a driving action of single component driving member, and which is driven to either a first region in which a image processing is not performed during said focusing operation, or a second region in which a image processing is performed during said focusing operation;

a discriminator for discriminating whether said zoom lens is moved to said first region or is moved to said second region;

a photo-electric converting element to receive a subject image incoming through said zoom lens, and to convert said subject image into image signals; and

an image processing section to output a first image data based on said image signals when said discriminator determines that said zoom lens is moved to said first region, or to output a second image data generated by applying a magnification change processing to said image signals based on predetermined zooming magnification factor when said discriminator determines that said zoom lens is moved to said second region.

Ab
cont

42. (Original) The camera of claim 2,
wherein said focal length changing operation is a zooming operation, and said focus adjustment is a focusing operation.

43. (New) A camera, comprising:

a first lens;

a second lens;

a photo-electric converting element to receive a light coming from a subject through said first lens and said second lens, and to convert said light into image signals;

a driving member to move said first lens and said second lens in an optical path;

a guiding member to guide said second lens moved by said driving member so that a distance between said photo-electric converting element and said second lens changes step by step corresponding to a plurality of predetermined positions of said guiding means;

a discriminator to discriminate a position of said second lens guided by said guiding member; and

an image processing section to apply an image processing, corresponding to a discrimination result outputted from said discriminator, to said image signals generated by said photo-electric converting element.

AB
cont

44. (New) The camera of claim 43,

wherein both a focal length changing operation and a focus adjustment are performed by means of said driving member.

45. (New) The camera of claim 43,

wherein said driving member selectively moves said second lens to one of said plurality of predetermined positions of said guiding member during a focal length changing operation.

46. (New) The camera of claim 45,

wherein said guiding member has a cam groove.

47. (New) The camera of claim 43, further comprising:

a display for displaying an image based on said image signals.

48. (New) The camera of claim 43,

wherein said image processing section outputs said image signals, generated by said photo—electric converting element, without applying said image-processing when said discriminator determines that said second lens is located at a first position, while said image processing section outputs processed image signals, acquired by applying said image processing, when said discriminator determines that said second lens is located at a second position.

Ab
cat

49. (New) The camera of claim 48,

wherein said image processing is an image-enlargement processing.

50. (New) The camera of claim 48,

wherein said first position is a reference position in each of zooming regions, while said second position is a predetermined focal position in each of said zooming regions.

51. (New) A camera, comprising:

a first lens;

a second lens;

a photo-electric converting element to receive a light coming from a subject through said first lens and said second lens, and to convert said light into image signals;

a driving member to move said first lens and said second lens in an optical path;

a guiding member to guide said second lens moved by said driving member so that a distance between said photo-electric converting element and said second lens changes step by step corresponding to a plurality of predetermined positions of said guiding means; and

Ab
emo a display for displaying an image based on said image signals;

wherein, when said driving member moves said first lens and said second lens, guided by said guiding member, in said optical path so as to conduct both a zooming operation and a focusing operation, said display displays said image based on said image signals acquired at each of predetermined focal positions.
